



MIR PART NUMBER: 9404057

General Information:

Product Description: M 150/1 0/U24 RED COS CONV BEL

Features: Abrasion Resistant, Bare Friction Surface

Market Segment: Metal Stamping, Foundry, Corrugated Boxes

Applications: -

Belt Construction:



Top Side (Material):	PU
Top Side (Surface):	Glossy
Top Side (Thickness):	0.16 in 4 mm
Top Side (Color):	Red
Top Side Shore:	85A Shore

Bottom Side (Material):	Polyester
Bottom Side (Surface):	Fabric
Bottom Side (Thickness):	- in - mm
Bottom Side (Color):	White
Bottom Side Shore:	-



Number of plies:	0
Weft:	Rigid

Technical Belt Data:

Foodgrade (FG):	Yes
Flame Retardant (FR):	No
Belt Weight:	- lbs/ft ² - kg/m ²
Belt Thickness:	0.25 in 6.35 mm
Tension Layer:	-
Pulley Diameter (minimum):	6 in 152.4 mm

Tensile Rating:	150 lbs/in
Working Temperature Range:	0 to 185 °F -18 to 85 °C
Hardness Topside:	85A Shore
Force at 1% Elongation (static) / k1% Relaxed:	- lbs/in - N/mm
Back Flexing:	- in - mm
Anti-Static:	No

Joining Method:

Mechanical Fasteners, Finger Splice

Additional Information:

