

MIR PART NUMBER: 9692

General Information:


Product Description:	M 150/2 0/R12 BLACK R/T CONV BELT
Features:	Abrasion Resistant, Excellent Adhesion, Excellent Flexibility
Market Segment:	-
Applications:	Light Duty Agriculture, Incline/Decline Packaging Conveying , Airport, General Conveying

Belt Construction:



Top Side (Material):	SBR	
Top Side (Surface):	Roughtop	
Top Side (Thickness):	- in	- mm
Top Side (Color):	Black	
Top Side Shore:	-	

Bottom Side (Material):	-	
Bottom Side (Surface):	Bare	
Bottom Side (Thickness):	- in	- mm
Bottom Side (Color):	Brown	
Bottom Side Shore:	-	



Number of plies:	2	
Weft:	-	

Technical Belt Data:

Foodgrade (FG):	No	
Flame Retardant (FR):	No	
Belt Weight:	1.1 lbs/ft ²	5.3 kg/m ²
Belt Thickness:	0.27 +/-0.02 in	6.73 +/-0.51 mm
Tension Layer:	-	
Pulley Diameter (minimum):	2 in	50.8 mm

Tensile Rating:	- lbs/in	
Working Temperature Range:	-40 to 250 °F	-40 to 121 °C
Hardness Topside:	-	
Force at 1% Elongation (static) / k1% Relaxed:	150 lbs/in	26.25 N/mm
Back Flexing:	- in	- mm
Anti-Static:	No	

Joining Method:

Mechanical Fasteners

Additional Information:

